

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



Clean Version of Pending Claims

2-DIMENSIONAL PLACEMENT WITH RELIABILITY CONSTRAINTS FOR LSI  
DESIGN

Applicant: Kiran Ganesh et al.

Serial No.: 09/431,477

RECEIVED  
APR 11 2002  
TECHNOLOGY CENTER 2800

- Sub B7  
A'
1. A computerized method of creating a layout for a circuit design, the method comprising:  
receiving a circuit design;  
receiving at least one layout rule based on a reliability verification constraint arising from self heat; and  
generating a layout for the circuit design through computer automated operations wherein the layout generated satisfies the at least one layout rule based on the reliability verification constraint received for the circuit design.
  2. The computerized method of claim 1, further comprising receiving at least one layout rule based on a reliability verification constraint arising from electromigration.
  4. The computerized method of claim 1, wherein the at least one layout rule defines a maximum current for a given wire width.
  5. The computerized method of claim 1, wherein the circuit design is a microprocessor circuit design.
  6. The computerized method of claim 1, wherein the layout is a two-dimensional layout comprising a plurality of overlapping rows.
  7. A computer automated placement method comprising:  
placing a plurality of components of an integrated circuit design in a layout for the integrated circuit design;
- A'

analyzing the layout for reliability verification considerations arising from self heat;  
rearranging the plurality of components to improve the reliability verification  
considerations; and

repeating the analyzing and the rearranging to further improve the reliability verification  
considerations.

8. The computer automated placement method of claim 7, wherein analyzing the layout for  
reliability verification considerations further includes analyzing for electromigration  
considerations.

---

10. The computer automated placement method of claim 7, further comprising analyzing the  
layout for other considerations selected from the group consisting of: layout density constraints,  
aspect ratio constraints, and routing complexity constraints.

11. The computer automated placement method of claim 7, wherein placing the plurality of  
components is done in a two-dimensional manner with a plurality of overlapping rows.

12. The computer automated placement method of claim 7, wherein analyzing the layout is  
performed by calculating an overall unidirectional current density for the layout.

13. A computerized method of placing a plurality of components of an integrated circuit in a  
layout, the method comprising:

assigning each one of a plurality of components of an integrated circuit to one of a  
plurality of clusters;

generating a layout for each one of the plurality of clusters;

placing each one of the plurality of clusters in a layout for the integrated circuit wherein  
the placing is performed in a two-dimensional manner with a plurality of overlapping rows;

analyzing the layout for the integrated circuit using a cost function having a reliability verification factor; and

rearranging the layout for the integrated circuit; and

repeating the analyzing and the rearranging until the cost function is minimized.

14. The computerized method of claim 13, wherein the reliability verification factor represents the effects of electromigration and self heat.

15. The computerized method of claim 13, wherein a width of each one of the plurality of overlapping rows is a multiple of a smallest one of the plurality of clusters.

16. The computerized method of claim 14, wherein assigning each one of the components is performed based on a lumped gate ordering style.

17. The computerized method of claim 14, wherein assigning each one of the components is performed based on a distributed gate ordering style.

18. The computerized method of claim 14, further comprising adjusting one or more of the plurality of components in one of the clusters to comply with a size constraint.

19. The computerized method of claim 18, wherein the adjusting is performed using device-based legging.

20. The computerized method of claim 18, wherein the adjusting is performed using stack-based legging.

21. The computerized method of claim 18, wherein the adjusting is performed using differential legging.

---

A<sup>3</sup>  
22. An article comprising:  
a computer-readable medium including instructions that when executed cause a computer to:  
receive a circuit design;  
receive at least one layout rule based on a reliability verification constraint arising from self heat; and  
generate a layout for the circuit design through computer automated operations wherein the layout generated satisfies the at least one layout rule based on the reliability verification constraint received for the circuit design.

---

23. The article of claim 22, wherein the reliability verification constraint arises from electromigration.

25. The article of claim 22, wherein the layout is generated in a two dimensional manner having a plurality of overlapping rows.

---

A<sup>4</sup>  
26. An article comprising:  
a computer-readable medium including instructions that when executed cause a computer to:  
place a plurality of components of an integrated circuit design in a two-dimensional layout for the integrated circuit design;  
analyze the layout for reliability verification considerations arising from self heat; and  
rearrange the components to improve the reliability verification considerations based on the analysis of the layout.

---

27. The article of claim 26, wherein the reliability verification consideration arises from electromigration.

A<sup>5</sup>  
29. A computer-readable medium having computer-executable modules comprising:  
a cell library to maintain a plurality of logic gates and a plurality of layout rules;  
a schematic design tool to create a schematic of an integrated circuit using the plurality of gates maintained by the cell library;  
a net list tool to create a net list representation of the schematic; and  
a placement tool to generate a layout of the integrated circuit from the net list representation wherein the placement tool performs a reliability verification of the layout for self heat considerations.

30. The computer-readable medium of claim 29 further comprising a routing tool to route wires between the plurality of logic gates in the layout.

A<sup>6</sup>  
31. A computerized system comprising:  
a computer-readable medium;  
a processor; and  
a computer-aided design program stored on the computer-readable medium and executable by the processor, the computer-aided design program comprising a placement module to generate a layout of an integrated circuit wherein the placement module performs a reliability verification of the layout for self heat and electromigration considerations.